Eco Mark Product Category No.128

"Household Commodity Version1.20" Certification Criteria Category A. Kitchen utensils and tableware

Japan Environment Association Eco Mark Office

1. Purpose of Establishing Certification Criteria

Commodities consist of various products, ranging broadly from kitchen utensils to tableware, home and living supplies, etc. They are the most closely related daily-use products to consumers. Setting an Eco Mark Category for such a group of commodities to recommend eco-friendly products within the category to consumers would therefore contribute enormously to reducing environmental impact in daily living, as well as enhance the environmental awareness of consumers. For this reason, the establishment of this Product Category is considered to have vast environmental significance.

Under the Eco Mark program, the certification criteria of several current product categories have been established taking material into account, namely Product Category No.115 "Wooden Products Using Waste Wood, Thinned-Out Wood, Small-Diameter Logs, etc.", No. 118 "Plastic Products Using Recycled Materials", and No.124 "Glass Products". This new Product Category was established by integrating the commodity products included in those product categories and adding tableware, kitchen utensils, footwear, and home and living supplies to cover a broad range of products.

Existed eight categories of the Eco Mark program cover kitchen utensils including sponges, coffee filters, cooking oil filters, rubber gloves, waste oil absorbers, draining filter bags, strainers, and triangle strainers for kitchen sinks. They have also been organized and integrated into this Commodity category. For these types of products, previous criteria were established from the environmental perspective of preventing discharge of water pollutants, using natural materials, and non-bleaching, but as a result of a general evaluation based on the new product lifecycle concept, they were reviewed also from the perspectives of effective use of resources and chemical substances this time.

As a specific example, Product Category No.5 "Absorbents for Used Cooking Oil" was established for the purpose of reducing waste by preventing the discharge of waste oil which causes water pollution and the use of recycled material, while in this Product Category, the effective use of thinned-wood and waste fiber (cloth, etc.) as unused material differing from recycled material was selected as a new criteria.

2. Applicable Scope

Applicable products of this Product Category are those shown in Attachment 1, selected out of the "Kitchen utensils and tableware, except silverware, plated ware

and similar metalware" covered by Standard Commodity Classification for Japan, issued by the Ministry of Public Management, Home Affairs, Posts and Telecommunications.

However, for products using electricity, and products whose weight percentage of metal materials, leather materials, and stone that make up more than 50% of the total product weight are excluded.

Table 1 Applicable product classification

Classification	ole product classifica				
number	Classification	Products applicable to each classification			
	KITCHEN UTENSILS AND TABLEWARE, EXCEPT SILVERWARE, PLATED WARE AND SIMILAR METALWARE				
	WARE AND SIMILAR METALWARE				
77 3271/77 3313/77 343/77 3513	Plates and dishes	Small plates, Gratin dish, dish for western style			
77 3311/77 3317/77 3321/77 341/77 3511/77 3512/77 39	Small Bowls	Soup bowls, Rice bowls,			
77 3272/77 3312/77 3322/77 342	Bowls for donburi	Donburi			
77 326/77 3324/77 3515/77 39	Bowls	Curry bowls, Soup bowls, Punch bowls, Salad bowls, Slop bowls, Mixing bowls			
77 326/77 3314/77 3315/77 3324/77 344/77 3514	Bowls	Shallow bowls, Bowls with lid, Café bowls			
77 321/77 322/77 323/77 324/77 325/77 3316/77 345/77 361/77 39	Tumblers (cup)	Jugs, Cocktail glasses, Champagne glasses, Brandy glasses, Whisky glasses, Cordial glasses, Sherry glasses, Wine glasses, Sundae glasses, Paffe glasses, Fruit punch glasses, Fruit cocktail glasses, Goblet glasses, Pilsner glasses, Soda glasses, Tea cups			
77 3291/ 77 3318/ 77 39	Vessels for sake				
77 39	Other tableware	Sauce board, Sundae cups, Casseroles, Mug cups with lid			
	Knives, forks, spoons,	ns, chopsticks and others			
77 613 77 614 77 39	Forks				
77 613/77 614/77 39	Spoons	Tea spoons			
77 39	Ladles				
77 39	Tongs				
77 612/77 39	Ceramic spoons				
77 621	Chopsticks	Lacquered chopsticks			
77 623	Chopsticks plates				
77 624	Chopsticks stands				
77 99	Other	Cake servers, Ice cream dishers, Cutlery cases, Fork rests			

3. Terminology

Terms for the common criteria					
Products not intended for repeated use while other					
products in the same area are used repeatedly with					
durability.					
Nature of products and packaging designed for					
repeated use for a certain number of times through					
recycling.					
Indicates material recycling. Does not include					
energy recovery (thermal recycling).					
Components intentionally added with the purpose					
of providing specific characteristics to the product.					
Impurities which are inevitably mixed during the					
manufacturing process are excluded.					
Plate-like thin plastic with 0.25mm and more					
thickness					
Materials made of post-consumer materials,					
pre-consumer materials, or a mixture of these. In					
this Product Category, includes waste fiber. Materials or defective products generated from					
disposal route of manufacturing process. However,					
excludes those recycled within the same process as					
the raw material (same plant).					
Materials or products disposed after used as a					
product.					
product.					
Weight percentage of waste pulp in pulp contained					
in product. Expressed by (waste paper pulp) /					
(virgin pulp + waste paper pulp) x 100 (%).					
However, the weight of the pulp is measured under					
the condition of containing 10% moisture. For					
materials with 100% yield such as pulp mold and					
cushioning made of cut waste paper, percentage of					
waste paper in pulp mixture is taken to be 100%					
regardless of the actual percentage.					
Indicates the following: thinned wood, waste wood,					
construction waste wood, and less useful wood.					
Wood produced from work estimities adjusting the					
Wood produced from work activities adjusting the individual density of the objective tree type according					
to the congested state of forest stand.					
Used wood (used packaging material, etc.),					
remainder material generated in wood processing					
plants (shavings generated in plywood and lumber					
plants, etc, low quality chips not used as raw					
plants, etc, low quality chips not used as law					
material for paper, etc.), and wood and wooden					
1 =					
material for paper, etc.), and wood and wooden					
material for paper, etc.), and wood and wooden materials such as trimmed branches, bark, etc.					
material for paper, etc.), and wood and wooden materials such as trimmed branches, bark, etc. Wood and wooden materials disposed as waste in					

	
Less useful wood	Abandoned lumber in the forest, shrubs, tree roots, wood obtained from lumber damaged by disease, pests, disasters, bent or small diameter logs, etc. Also includes bamboo cut down in bamboo groves for the purpose of maintenance and management in environment preservation. Small diameter logs measuring less than 14 cm in diameter corresponding to "a" or "b" below must be certified as forests sustainably managed by an independent third party. a. Small diameter logs from logs felled from natural forests. b. Small diameter logs from logs produced by clear cutting, patch logging, and strip logging in plantation forests.
Waste plant fiber	Fiber made from agricultural residue (such as
waste plant liber	stalks that are usually disposed, etc.) generated in
	harvesting and manufacturing process of crop.
Wooden part	Actual wood (including plant fiber)
Terms for plastic	Tiotaan wood (morating plant moor)
Plastic	Materials made of single or multiple polymers,
1 143,010	additives, fillers, etc. added to give characteristics
Polymer	Macromolecules, which are the main
, and the second	components of plastic.
Plant-based plastic	Plastic made of bio-based synthetic polymer whose materials are plant. This certification criteria covers polyethylene (PE), polyethylene terephthalate (PET), polylactic acid (PLA) and polytrimethylene terephthalate (PTT).
Bio-based synthetic	Polymer obtained through chemical and/or
polymer	biological industrial process(es) wholly or partly from biomass resources.
Bio-based synthetic	Amount of biomass resource origin part in biobased
polymer content rate	synthetic polymer present in the product (or the portion specified in the certification criteria). Natural polymers such as starch are not included. This is defined in ISO 16620-1 3.1.5. (original biobased synthetic polymer content amount of biobased synthetic polymer present in the product.)
Terms for glass	
Glass cullet content	Percentage of glass cullet in the whole glass materials used in a product. i.e. Glass cullet content = Glass cullet/Whole glass materials (per product), (materials are expressed in weight)
Cullet	Glass materials recycle-processed (sorting, elimination of foreign bodies, etc.) from waste glass

4. Certification Criteria and Certification Procedure

To show conformance to the individual criteria item, the respective Attached Certificates shall be submitted.

4-1. Environmental Criteria and Certification Procedure

4-1-1. Common Criteria and Certification Procedure

(1) In manufacturing the applied product, related environmental laws and regulations and pollution control agreement (hereinafter referred to as the "Environmental Laws, etc.") must be followed with respect to air pollution, water contamination, noise, offensive odor, and emission of hazardous substances in the area where the plant performing the final manufacturing process is located.

In addition, the state of compliance with the Environmental Laws, etc. for the past five years from the date of application (whether there is any violation) must be reported. If there is any violation, proper remedies and preventive measures shall have been already taken, and the related Environmental Laws, etc. must thereafter be followed appropriately.

[Certification Procedure]

With respect to the compliance with the Environmental Laws, etc. in the area where the plant performing the final manufacturing process is located, a certificate issued by the representative of the business of manufacturing the applied product or the relevant plant manager (entry or attachment of a list of names of the Environmental Laws, etc.) must be submitted.

In addition, the applicants shall report whether there is any violation in the past five years, including a violation subject to administrative punishment or administrative guidance, and if there is, the following documents in a and b must be submitted:

- a. With respect to the fact of violation, guidance documents from administrative agencies (including order of correction and warning) and copies of written answers (including those reporting causes and results of correction) to such documents (clearly indicating a series of communication);
- b. Following materials (copies of recording documents, etc.) concerning the management system for compliance with the Environmental Laws, etc. in 1)-5):
- 1) List of the Environmental Laws, etc. related to the area where the plant is located;
- 2) Implementation system (organizational chart with roles, etc.);
- 3) Bylaws stipulating retention of recording documents;
- 4) Recurrence prevention measures (future preventive measures);
- 5) State of implementation based on recurrence prevention measures (result of checking of the state of compliance, including the result of onsite inspection).
- (2) Products shall not increase waste (products shall not be disposable).

[Certification Procedure]

The use of the applied product shall be indicated in the Attached Certificate.

(3) Products shall consist of less than 50% metal for the total product weight.

[Certification Procedure]

The total weight of metals used in the applied products shall be indicated in the Attached Certificate.

(4) Products shall be shipped in the unpackaged state or in simple packaging at the retail stage. Material labeling of plastic materials used for packaging shall conform to JIS K 6899-1:2000. However, labeling can be omitted in accordance with the standards on ID marks in the "report developed by the Package Labeling Review Committee" (Ministry of Economics, Trade and Industry) such as "labeling for plain containers", "labeling for containers with physical restrictions of display space, etc.", "labeling conditions and methods for multi-layer containers, etc.", "labeling for packaging printed with company/brand name", and "labeling on export products".

[Certification Procedure]

The packaging state in the retail stage of products, packaging material used (content rate of recycled materials), material labeling state shall be indicated in the Attached Certificate. (Drawings and photographs can be used to supplement description). If material labeling is omitted, the reason shall be indicated.

(5) Plastic materials used for packaging shall not be added with polymers including halogens, and organic halogenides shall not be added to products as prescription constituents.

[Certification Procedure]

Whether polymers including halogens and organic halogenides have been added to packaging shall be indicated in the Attached Certificate.

(6) The product shall not use antimicrobial agents as far as possible. In the case of use, the product shall be certified by the SIAA Mark of Society of Industrial technology for Antimicrobial Articles or the SEK Mark of Japan Textile Evaluation Technology Council, etc.

[Certification Procedure]

Compliance with this item shall be indicated in the Attached Certificate.

In the case of using antibacterial agents, documents certifying SIAA Mark of Society of Industrial technology for Antimicrobial Articles, or SEK Mark of Japan Textile Evaluation Technology Council, etc. shall be submitted.

4-1-2. Material criteria and Certification Procedure

Materials of which the product is composed shall meet the material criteria specified below. However, the following material criteria shall not apply to small accessories (screws, shoestrings and other small parts required by the product function) and (14) shall apply to adhesive and the other material criteria shall not apply to adhesives.

A. Paper

(7) Percentage of waste paper in the pulp mixture shall be above 70%.

- (8) The coating amount on coated printing paper shall be 30 g/m² or less on both sides. However, the maximum amount per side shall be 17g/ m².
- (9) The brightness of uncoated printing paper shall be about less than 70%.
- (10) Addition of fluorescent whitening agents as a prescription constituent shall be minimized.
- (11) Chlorine gas shall not be used in the bleaching process of pulp.

[Certification Procedure]

Certificates issued by the paper manufacturer shall be submitted. For (7) and (8), the waste paper pulp content, and specific coating amount (numerical value) on either and both sides shall be indicated. Documents indicating the results of brightness tests by the Hunter method or based on the ISO whiteness (diffuse blue reflectance factor) shall be submitted. These documents shall indicate the specific whiteness value for the test results, whether florescent whiteners are added. If added, the amount used in the documents submitted.

Whether chlorine has is used in the pulp whitening process shall be indicated.

B. Wood

(12) The percentage of reused/unused wood or waste plant fiber provided by terminology as materials for wooden parts shall be 100% (weight percentage). Less useful wood with small diameters shall satisfy Attachment 1 for forest certification if corresponding to "a" or "b".

(Note) The weight percentage means the weight percentage of the product or each material at the air dried state*1 or at the point of constant weight*2 under the condition of a temperature of 20±2°C and humidity of 65±5%.

- *1: Indicates leaving in a well-ventilated room for seven days or more.
- *2: Change is less than 0.1% when weight is measured every 24 hours.
- *1 is not applicable if lumber and logs are used. It can be applied when using wood corresponding to the water content percentage of 15% or below in domestic and overseas public dried material water content percentage criteria.

[Certification Procedure]

Documents issued by the raw material vendor certifying that the raw material is reused /unused wood or waste plant fibers shall be submitted. If there are multiple vendors, a list of the vendors and list of certification of the top 10 vendors in terms of volume of material traded shall be submitted.

If using thinned wood as the material, a certificate of origin that includes information on the place of production, type of tree, and year of planting shall be submitted with photographs of the forest concerned (showing clearly that the forest stand has been thinned). The thinning percentage and how many times the forest stand has been thinned, including the most recent thinning shall also be indicated if possible.

If using less useful wood, the following information shall be submitted. At the same time, official documents stating that the forest has been certified as sustainable by a third party shall be submitted.

• Type of forest (natural or man-made, etc.), place of production, type of tree, and year of tree planting if man-made forest.

- Under what conditions was the wood produced (damaged by disease/pests, damaged by disaster, bent or narrow trees, etc.). For small diameter log, indicate logging method and tip end diameter.
 - If using bamboo as the raw material in less useful wood, certificates indicating the following information and photographs/maps of the surroundings of the bamboo grove shall be submitted.
- Type of bamboo, place of production, surrounding conditions, and description that logging is carried out for the purpose of appropriate maintenance and management in environment preservation, as well as management plans and quantity.
- (13) Products shall not use wood preserving agents (wood termicides, preservatives, pesticides, and fungicides) as prescription constituents.

[Certification Procedure]

Whether termicides, preservatives, and pesticides are used as prescription constituents shall be indicated in the Attached Certificate.

(14) Regarding products used indoors, no emissions of toluene or xylene shall be detected at product shipment. "No emissions detected" means less than the minimum value measured by JIS A 1901. "Measuring methods for emission of volatile organic chemicals (VOC), formaldehyde and other carbonyl compounds—small chamber method."

[Certification Procedure]

Results of tests prescribed in JIS shall be submitted. The test method shall be based on JIS A 1901. However tests can be exempted for products not added with toluene and xylene as prescription constituents.

- (15) For products used indoors and using adhesive or paint, emissions of formaldehyde from the product, wood material, adhesive or paint shall be of the F**** grade in accordance with JIS or JAS, or falling outside the scope of regulations by the Ministry of the Land, Infrastructure and Transport. The products should meet the numerical criteria of "a" or "b" below. However, this item is not applied to "incense stick".
 - a. The amount of Formaldehyde emissions measured by JIS A 1460 "Building boards Determination of formaldehyde emission -- Desicator method" shall be below 0.3 mg/l for average value and below 0.4 mg/l for maximum value.
 - b. The emission rate of formaldehyde measured by JIS A 1901 "Determination of the emission of volatile organic compounds and formaldehydes for building products -- Small chamber method" shall be less than 5µg/(m2-h).

[Certification Procedure]

Results of tests prescribed in JIS A 1460 or JIS A 1901 or tests by methods prescribed in specific JIS or JAS criteria shall be submitted to indicate that standard values are met. For materials and products permitted to be labeled F**** grade in accordance with JIS and JAS, documents certifying this or copies of such documents can be submitted in place of test results. For materials and products authorized as falling outside the scope of regulations by the Ministry of

Land, Infrastructure and Transport, documents certifying this or copies of such documents can be submitted in place of test results. For materials and products permitted to be labeled as using non-formaldehyde adhesives by JAS, documents certifying this or copies of such documents can be submitted in place of test results.

C. Plastic

(16) Weight percentage of recycled polymer in the total raw material polymer of the product shall be over 50% for products made of post-consumer materials as the raw material polymer. However, for products made of pre-consumer materials as the raw material polymer, weight percentage of recycled polymer made from pre-consumer materials in the total raw material polymer of the product shall be over 60%.

Products using plant-based plastic shall meet the criteria item (17) instead of this item

[Certification Procedure]

The weight percentage of pre-consumer materials and post-consumer materials making up the whole product shall be indicated in the Attached Certificate. Raw material certificates issued by the raw material supplier shall also be attached.

- (17) Products using plant-based plastic shall meet all requirements in the following a) to c). Regarding plant-based synthetic plastic, PE, PET, PLA and PTT shall be applicable.
 - a) The content of bio-based synthetic polymer in the product shall be equal to or higher than 25%;
 - b) The Applicant shall have the understanding of the supply chain from cultivation of plant materials to manufacturing of plant-based plastic (raw resin). Each process shall conform to the checklist in the Attachment 2; and
 - c) The Applicant shall have confirmed by the life cycle assessment (LCA) that for the plant-based plastic (raw resin), greenhouse gas emissions (CO₂ conversion) from raw material procurement to discarding/recycling does not increase, when compared with conventional resin that is to be replaced. Note that if any increase in the emissions is offset by the reliable carbon offset (such as purchasing clean electric power, etc.), the applied product shall also conform to this item.

[Certification Procedure]

a) Certificates indicating the calculated content of bio-based synthetic polymers in the product shall be submitted. For the plant-based plastic (raw resin) thereof, measurement results of the bio-based synthetic polymer content calculated with the method specified in ISO 16620-3, using measurement results of the bio-based carbon content and element composition by the 14C method specified in ISO 16620-2 or ASTM D6866 shall be mentioned. Should there be any deviation of 10% or higher between the measurement results and the content of bio-based synthetic polymer in the standard, a description of a reason(s) therefor shall also be included. The measurement results of the bio-based carbon content shall be submitted as an attached document.

In addition, for appropriate maintenance of the content of bio-based synthetic polymer after certification, any of the following certificates issued by a raw resin

supplier (including a dealer) shall be submitted.

- An explanatory document stating that measurements of the content of bio-based carbon will be regularly carried out, and that measurement results can be disclosed as per a request of the Eco Mark Office; and
- A certificate that the Applicant has been audited or certified by a third party for management of the content of the bio-based synthetic polymer.
- b) Certificates issued by a raw resin supplier (including a dealer) indicating the supply chain (flow diagram, etc. and including purification, fermentation, etc.) from the cultivation area (country, state, city, etc.) to manufacturing of plant-based plastic (raw resin), and status of conformance to the Attachment X shall be submitted.
- c) Results of the LCA assessment of the plant-based plastic (raw resin) shall be submitted (reference to the existing paper, etc. is acceptable). If carbon offset is adopted, data describing content of the carbon offset and reliability shall be submitted together.
- (18) HCFCs shall not be used during the manufacture of plastic materials.

[Certification Procedure]

Certificates issued by the manager of the plant manufacturing the plastic material shall be submitted.

(19) Polymers including halogens and organic halogen compounds shall not be added to plastic products as prescription constituents.

[Certification Procedure]

Whether polymers including halogens and organic halogenides have been added to packaging shall be indicated in the Attached Certificate.

(20) Products shall not contain harmful substances such as heavy metal, etc. prescribed in laws and voluntary criteria of the industry concerned as prescription constituents.

Plastic additives shall conform to the positive list prescribed in the voluntary criteria of each industry such as the Japan Hygienic Olefin And Styrene Plastics Association.

The plastic color material shall conform to the "color material criteria" of the Japan Hygienic Olefin And Styrene Plastics Association for the content and emissions of heavy metal, etc.

[Certification Procedure]

Certificates issued by the raw material supplier, or documents certifying results of tests performed by a third party testing center or public institution shall be submitted. However, if all the raw materials used do not contain the corresponding chemical substances as prescription components, documents certifying this issued by the raw material suppliers or applicant can be submitted instead.

(21) The product shall not contain Polybrominated biphenyl (PBB), Polybrominated diphenylether (PBDE) or short-chain chlorinated paraffin (the number of chained C is 10 to 13 and contained chloride concentration is 50% or over) as a

prescription constituent when flame retardant is used in plastics.

[Certification Procedure]

Compliance with this item shall be indicated in the Attached Certificate. In the case of using flame retardant, the applicant shall submit a document specifying the names of chemical substances.

D. Glass

(22) Use of glass cullet shall be above 70% (weight percentage). It shall be above 20% (weight percentage) in heat-resistant glass.

[Certification Procedure]

The utilization rate of glass cullet and weight percentage of glass materials making up the whole product shall be indicated in the Attached Certificate.

(23) Safety of the glass bottle (elution of total mercury, chromium, arsenic, selenium) shall be verified and explained. The elution of the subject materials shall conform to the requirement of the Environmental Standard concerning soil pollution (the Ministry of Environment Notice No.46, Aug.23, 1991)).

[Certification Procedure]

Purchasing methods and acceptance test standards (for cadmium, lead, mercury, chromium, arsenic, and selenium; tests may not be required for certain substances) of glass cullet shall be submitted.

(24) Coloring agents used in products shall not contain cadmium, lead, mercury, hexavalent chromium, arsenic, selenium and their compounds as prescription constituents.

[Certification Procedure]

Component list issued by the manufacturer of coloring agents or the Material Safety Data Sheet (MSDS) shall be submitted.

E. Rubber

(25) The weight percentage of recycled rubber out of the total rubber used in the product shall be above 10%. However, this shall be over 60% for normal temperature molded products using rubber powder.

[Certification Procedure]

The weight percentage of recycled rubber materials making up the total rubber weight shall be indicated in the Attached Certificate. Raw material certificates issued by raw material suppliers shall be attached.

(26) Harmful substances contained in rubber shall conform to criteria on heavy metals prescribed in the Ministry of Environment Notice No.46, Aug.23, 1991.

[Certification Procedure]

Certificates issued by raw material suppliers and documents certifying results of tests implemented by a third party testing center or public institution shall be submitted. However, if all the raw materials used do not contain the

corresponding chemical substances as prescription components, documents certifying compliance with this criterion issued by the raw material suppliers or applicant can be submitted instead.

(27) The product shall not contain Polybrominated biphenyl (PBB), Polybrominated diphenylether (PBDE) or short-chain chlorinated paraffin (the number of chained C is 10 to 13 and contained chloride concentration is 50% or over) as a prescription constituent when flame retardant is used in rubber.

[Certification Procedure]

Certificates issued by raw material suppliers and documents certifying results of tests implemented by a third party testing center or public institution shall be submitted. However, if all the raw materials used do not contain the corresponding chemical substances as prescription components, documents certifying compliance with this criterion issued by the raw material suppliers or applicant can be submitted instead.

(28) Information on appropriate handling of products such as precautions on handling and storage and allergy information, etc. shall be provided in instruction manuals, on product labels, and in pamphlets.

For labeling of allergy information on products, the following requirements shall be observed:

- a. In material labeling, name of materials related to natural rubber, rubber, or plastic shall be indicated. For synthetic rubber and plastic, indicate the specific name in brackets behind the name of the material.
 - Example: Synthetic rubber (nitrile rubber), natural rubber
- b. For synthetic rubber, natural rubber and plastic products, in addition to the current precautions on use, also include precautions on use for allergy referring to Example 1 below. For natural rubber products, in addition to the current precautions on use, also include precautions on use for latex allergy referring to Example 2.
 - Example 1: May cause itchiness, skin irritation, rash. In such cases, discontinue use.
 - Example 2: This product is made of natural rubber. Natural rubber can rarely cause itchiness, redness, rash, bloating, fever, difficulty in breathing, asthma-like symptoms, drop in blood pressure, shock, and other allergic symptoms. In such cases, discontinue use promptly and consult your physician.

[Certification Procedure]

Labeling of allergy information shall be indicated specifically in the Attached Certificate. (Drawings and photographs can be used to supplement description)

F. Ceramics

(29) For ceramics, for each raw material category given in Table 3, the weight of

recycled materials in the total weight of the product shall meet the Standard Mixture Amount shown. However, for products made of several recycled materials so that they apply to several Standard Mixture Amount in Table 3 below, the total weight percentage of all recycled materials shall be above the standard mixture amount shown. The Standard Mixture Amount lower limit is calculated using the following equation based on the proportional composition.

Standard Mixture Amount (lower limit of recycled material)(%) = (AxX1+BxX2)/(A+B)

(Set for products using [Standard Mixture Amount X1% category material] = A% and [Standard Mixture Amount X2% category material] = B%)

Table 2 Raw Material Categories of Recycled Materials, Certification on Use, and Standard Mixture Amount

Category and name of of rec	Standard Mixture Amount ^{Note2)}		
Category	Name of recycled material	(Weight%)	
Waste from mines ceramics and quarries -Waste sand from quarries and ceramics -Micro silica sand generated a separation of silica by water		35%	
Used pottery	15%		
Glass cullet	Glass weight/product weight $\geq 15\%$ Glass cullet use rate $\geq 70\%$		
Other industrial waste	-Coal ash -Shell	50%	

Note 1) For products in which a small amount of colorant is added to molten parts, the weight of colorant shall not be included in the weight of all materials used for calculating the standard mixture amount.

Note 2) For the products containing moisture, use dry weight, and for fired and molten products, the weight loss on burning shall not be included.

Note 3) For products applicable to several standard mixture amounts in this table due to multiple recycled materials used, calculate the standard mixture amount on a proportional basis.

Example) Fired and molten parts using ceramic waste and sewer sludge

Ceramic waste A (%)(Standard mixture amount 35%)

Used pottery B (%) (Standard mixture amount 15%)

In this case, the standard mixture amount (lower limit of recycled material content) (%) is (Ax35+Bx15)/(A+B).

Consequently, in this case, the A+B total content rate is required to be above the standard mixture amount calculated in the above equation.

Note 4) For products using glass cullet in the raw material category in Table 3, the weight percentage of glass materials making up the product weight shall be above 15%, and the rate of using glass cullet shall be 70%.

[Certification Procedure]

The standard mixture amount and total weight percentage of the recycled materials shall be indicated in the Attached Certificate for each raw material category in Table 2. Raw material certificates issued by raw material suppliers shall be attached.

4-1-3. Criteria on individual products and certification procedure

(30) Information on appropriate handling of products such as precautions on handling and storage, etc. shall be provided in instruction manuals, on product labels, and in pamphlets.

[Certification Procedure]

Copies of instruction manuals, product labels, pamphlets, etc. providing information on handling and storage precautions shall be submitted.

(31) The product shall conform to the elution test for cadmium and lead as defined in the Food Sanitation Act. In addition, for food apparatus using waste paper or recycled plastic, the measures to ensure the safety based on the basis of Ministry of Health, Labour and Welfare "Guidelines on the use of recycled paper in food apparatus and containers and packaging" (Shokuan, 0427 No.7, April 27 2012) or "Guidelines on the use of recycled plastic materials in food apparatus and containers and packaging" (Shokuan, 0427 No.2, April 27 2012) shall be taken.

[Certification Procedure]

Results of tests based on the Food Sanitation Act shall be submitted. In addition, for food apparatus using waste paper or recycled plastic, the written document shall be submitted which shows the ensuring of the safety on the basis of Ministry of Health, Labour and Welfare "Guidelines on the use of recycled paper in food apparatus and containers and packaging" or "Guidelines on the use of recycled plastic materials in food apparatus and containers and packaging".

4-2. Quality criteria

(32) The product quality shall conform to Japanese Industrial Standard, Japan Agricultural Standards and the industry quality standards. In addition, the quality control is adequately implemented in the manufacturing stage.

[Certification Procedure]

Certificates of compliance with the corresponding quality criteria shall be submitted. At the same time, certificates and declarations issued by the manager of the plant manufacturing the product that quality control is implemented in the manufacturing stage and shipped that only products passing quality inspections are shipped shall be submitted. If the applied product or the manufacturing plant of the applied product is JIS or JAS certified, submission of a photocopy of such JIS or JAS certification shall be sufficient for certification of conformance to this item.

5. Considerations

In manufacturing products, it is desirable to consider the following, although they are not requirements for certification. The conformance to the individual criteria item shall be indicated in Attached Certificates.

- (1) Products shipped in simple packaging shall meet the following criteria for packaging material.
 - a. Percentage of waste paper in the pulp mixture shall be above 70%
 - b. Weight percentage of recycled polymers in the total raw material polymers used in plastic sheets shall be above 60%.

6. Product Classification, Indication and Others

- (1) Products shall be classified by the sub-category purposes indicated in 2. Applicable Scope, and by brand or series name.
- (2) Environmental information for each product category shown in Table 3 shall be indicated below the mark. The environmental information indicated shall be consisted of two lines and enclosed in a rectangular box. However, the indication of Eco Mark and certification information (Type B indication) can be allowed by following "Guide to Eco Mark usage" (enforced on March 1, 2011). The location and details of the Eco Mark to be indicated shall be submitted when applying for Eco Mark product certification and use.

For Eco Mark products certified under Eco Mark Product Category No.118 'Plastic Products Using Recycled Materials' or No.124 'Glass Product' and those which conclude Eco Mark contract under this product category after April 1, 2005, the display of environmental information below mark which is used in the former product category may be indicated the same as before.

Table 3: omitted.

(3) The Eco Mark indication method shall be followed in accordance with "Guide to Eco Mark Usage".

Established: July 1, 2004 (Version 1.0)

Revised: Oct 14, 2004, Applicable Products, etc (Version1.1)

Revised: May 13, 2005, 4-6(1) and Attachment 1 (Version1.2)

Revised: Sept. 8, 2005, 4-1-2.(15) (Version 1.3)

Revised: October 19, 2006, 4.(23)-(26), 4.(51)-(54), 6(2) (Version 1.4)

Revised: April 13, 2007, 4-1-2.(15) (Version 1.5)

Revised: August 2, 2007, 4-1-3.(42) (Version1.6)

Revised: Oct. 5, 2007 Extension of Term of Validity

Revised: Feb. 14, 2008, (Version 1.7)

Revised: August 21, 2008, (Version 1.8)

Revised: May 1, 2009, (Version 1.9)

Revised: November 4, 2009, (Version 1.10)

Revised: December 13, 2010, (Version1.11)

Revised: March 1, 2011, (Version1.12)

Revised: August 1, 2011, (Version 1.13)

Revised: November 1, 2011, (Version1.14) Revised: February 1, 2012, (Version1.15) Revised: July 5, 2012, (Version1.16)

Extension of Expiration date: February 1, 2014

Revised: June 1, 2015, (Version1.17) Revised: June 1, 2016, (Version1.18) Revised: February 1, 2017, (Version1.19) Revised: September 1, 2017, (Version1.20)

Expiration date: June 30, 2020

The Certification Criteria for the Product Category will be revised when necessary.

Attachment 1 Forest Certification defined in Terminology

Contification with a	- Ci			
Certification criteria	Certification shall keep balance between ecological and			
	social benefits, agree to Agenda 21 and the Declaration			
	of Forest Principle, and observe related international			
	agreements and treaties.			
	Certification shall contain definite requirements and			
	shall promote and be oriented to sustainable forest.			
	Certification shall be nationally or internationally			
	recognized and shall be recommended as part of an			
	open process to which ecological, economic, and social			
	interested parties can participate.			
Certification system	The certification system shall provide high			
	transparency, maintain extensive national or			
	international reliability, and enable the verification of			
	requirements.			
Certification	Certification organization and association shall be			
organization and	highly impartial and reliable, allow them to be verified			
association	as to whether or not they satisfy requirements, report			
	the verification results, and be able to effectively			
	implement requirements.			

Attachment 2 Checklist of Traceability of Plant-based Plastic (Raw Resin)

No	Purpose	Request (Item that must be realized)	Subject	Realized	Implementation Method (Check off all relevant items.)
1	Prevention of global warming, conservation of the natural ecosystem	Hasn't the farm land where plants are cultivated been converted from forests in the recent ten years?	Farm land	□Yes/ □No	□Confirmed the laws and regulations concerning the land conversion for the site. □Gained the understanding of the actual condition of the site through on-site investigation or hearings. □Defined and released the guideline for procurement of plants. Alternatively, conforming to the guideline of an independent third party. - Name of the guideline: - Location of release: □Also using the certification system of an independent third party, regarding the procurement of plants. -Name of certification system: □Others (Describe specifically.):
2	Conservation of the ecosystem	If the Applicant uses the genetically engineered crop as a raw material, has the Applicant assessed ensuring of safety?	Farm land	□Yes/ □No/ □Not applicable (Not used)	□Confirmed the laws and regulations concerning genetically engineered crop on the site. □Gained the understanding of the actual condition of the site through on-site investigation or hearings. □Defined and released the guideline for procurement of plants. Alternatively, conforming to the guideline of an independent third party. - Name of the guideline: - Location of release: □Also using the certification system of an independent third party, regarding the procurement of plants. -Name of certification system: □Others (Describe specifically.):

No	Purpose	Request (Item that must be realized)	Subject	Realized	Implementation Method (Check off all relevant items.)
3	Prevention of land acidification/nutrient enrichment/water contamination		Farm land	□Yes/ □No	□Confirmed the laws and regulations concerning fertilizers/agricultural chemicals on the site □Gained the understanding of the actual condition of the site through on-site investigation or hearings. □Defined and released the guideline for procurement of plants. Alternatively, conforming to the guideline of an independent third party Name of the guideline: - Location of release: □Also using the certification system of an independent third party, regarding the procurement of plantsName of certification system: □Others (Describe specifically.):
4	Appropriate water usage	Has the Applicant gained the understanding of usage conditions of water in the main cultivation area of plants?	Farm land	□Yes/ □No	□Confirmed the laws and regulations concerning usage of water (limits on the amount of water) on the site. □Gained the understanding of the actual condition of the site through on-site investigation or hearings. □Defined and released the guideline for procurement of plants. Alternatively, conforming to the guideline of an independent third party. - Name of the guideline: - Location of release: □Also using the certification system of an independent third party, regarding the procurement of plants. -Name of certification system: □Others (Describe specifically.)

No	Purpose	Request (Item that must be realized)	Subject	Realized	Implementation Method (Check off all relevant items.)
5	Use of recycled resources, avoidance of competition for food	part of crude raw materials of	Raw resin	□Yes/ □No/ □Not applicable (Not available)	Name of recycled resource in use [
6	Prevention of global warming	Has the Applicant gained the understanding of the processing status of biogas (such as methane) having a high global warming potential that is generated in the course of reaction of plant-based ethanol in the manufacturing plant for the main crude raw material?	Crude raw material manufacturing plant	□Yes/ □No	□Gained the understanding of the actual condition of the site through on-site investigation or hearings. □Others (Describe specifically.) []
7	Utilization of non-fossil energy sources and renewable energy sources	If a plant is newly set up in the course of cultivation to raw resin manufacturing, did the Applicant utilize as many non-fossil energy sources (for example, bagasse or biogas) or renewable energy sources as possible?	Manufacturing plant	□Yes/ □No	Energy name and method of utilization []
8	Legal compliance	Is discharged water in the plant controlled in accordance with the laws and regulations of the region, etc., where the plant for manufacturing the plant-based plastic (raw resin) is located?	Resin manufacturing plant	□Yes/ □No	Attach data describing the control of discharged water of the plant